

Drainage Report for
Structure E-15-AH
SH 170 OVER SOUTH BOULDER CREEK



Prepared for:
Colorado Department of Transportation

Prepared by:
Hydrau-Tech, Inc.

May 2013



&



ACKNOWLEDGEMENTS

In 1991 the FHWA required all states to provide Plans of Action (POAs) for scour critical bridges. In November 1998 the FHWA reported that CDOT had completed the implementation of POA for its Scour Critical Bridges. Due to a recent, nationwide mandated requirement by FHWA, CDOT was tasked to re-evaluate and update the POAs for each of the 243 bridges identified by CDOT as scour critical or structures with unknown foundations. To complete this task, CDOT created a program to address the scour critical bridges and appointed a consultant team led by RESPEC (previously Moser & Associates Engineering) in partnership with HYDRAU-TECH, Inc. to develop the POAs. The overall goals of the program were:

- For each scour critical bridge, complete a POA.
- For bridges with unknown foundations, identify the depth and type of substructure and determine the potential scour.

For the POA implementation, FHWA requires a multi-disciplinary team with expertise in hydraulics, structural, and geotechnical engineering. In addition to FHWA multi-disciplinary team, CDOT has recognized the importance of other fields such as maintenance, environmental, and construction and has added members with expertise in these fields. Members with maintenance expertise were to address historical flood and maintenance concerns; members with environmental expertise were to address cases where scour countermeasures could have adverse impacts on river habitat; and finally, members with construction and design expertise was added to aid in the detail and setup of construction projects for POA and scour countermeasure implementation.

This POA report was prepared by Hydrau-Tech, Inc. under the direction of Dr. Albert Molinas, President, Hydrau-Tech, Inc. The project engineers who participated in the study and in the preparation of the Hydrau-Tech, Inc.'s POA reports were Mr. William Bailey, Dr. Christopher Thornton, Dr. Chester Watson, Mr. Dustin London, and Mr. Brett Sollenberger. Mr. Adam Pierce, Watershed Scientist, managed the hydraulic surveying and data collection efforts, and was in charge of coordinating between various elements of the study. Mr. Adam Pierce, Mr. Brett Sollenberger, Mr. Tyler Liebman, Mr. Dustin London, and Mr. Jawid Ebadi participated in data collection, sediment analysis, and drafting. Ms. Maggie Molinas edited the Hydrau-Tech, Inc. reports. The structural analysis for the study was conducted by Mr. Dan Bechtold, Vice-President, LONCO Inc. The geotechnical analysis of foundation materials was conducted by Mr. Paul Macklin, YEH and Associates, Inc. Mr. David Delagarza and Mr. Josh Morin, Moser & Associates Engineering provided assistance in the fields for cost analysis, identifying data sources, and structural detailing of countermeasures. Hydrau-Tech, Inc. would like to acknowledge the support and valuable contributions of many individuals involved in the preparation of this report and during the various

phases of the POA study including the members of the CDOT Headquarters/FHWA Multi-Disciplinary POA Team and the members of the Field Inspection and the POA Review Team. Hydrau-Tech, Inc. would also like to acknowledge Mr. Rick Moser, RESPEC for his skillful leadership as the Project Manager for the Consultant Team. Special thanks go to Mr. Amanullah Mommandi, CDOT Project Manager, who was the Technical Reviewer of the project. His vast knowledge in hydraulics and scour countermeasures greatly benefited the study. He participated in all site inspection visits, made valuable countermeasure suggestions, organized the POA review meetings, and coordinated the CDOT Headquarters/FHWA Multidisciplinary POA Team meetings, the field inspections, and regional POA Draft report reviews.

The individuals who participated in the POA study and contributed to this report were:

CDOT Project Manager:

Amanullah Mommandi, CDOT Hydraulic Program Manager

CDOT Headquarters/FHWA Multi-Disciplinary POA Team Members:

Amanullah Mommandi, Chair, CDOT Hydraulic Program Manager

Mark Leonard, CDOT Staff Bridge

Timothy Ashenberger, CDOT Project Development

Mark Nord, CDOT Staff Bridge, Management Systems

Jeff Anderson, CDOT Staff Bridge, Inspections

Dave Weider, CDOT Maintenance

C. K. Su, CDOT Geotechnical, Soils and Rockfall

Tom Boyce, CDOT Environmental

Matt Greer, FHWA Structural/Materials Engineer

Field Inspection and POA Review Team Members:

Region 1:

Trever Wang – Staff Bridge, Region 1 & 5

Steve Yip – Staff Bridge, Region 1

Alfred Gross – Region 1, Hydraulics Engineer

Mike DeLong – Region 1, Region Maintenance Superintendent

Larry Dungan – Region 1, Transportation and Maintenance Supervisor

Steve Alderman – Region 1, Staff Bridge, Bridge Coordinator

John Gregory – Region 1, Staff Bridge

Curtis Johnson – Region 1, Maintenance

Region 3:

Behrooz Far – Region 3, Staff Bridge
Stuart Gardner – Region 3, Hydraulics Engineer
Peter Mertes – Region 3, Region Program Engineer
Jason Smith – Region 3, Region Program Engineer
John David – Region 3, Deputy Maintenance Superintendent
Todd J. Blake – Region 3, Traffic, Transportation Maintenance
Hans Egghart – Region 3, Professional Engineer I
Scott Marsh – Region 3, Maintenance
Stephen Bokros – Region 3, Engineer

Region 4:

Richard Osmun – Region 4, Staff Bridge
Tom Moss – Region 4, Staff Bridge
Hoang Bui – Region 4, Staff Bridge
Steven Griffin – Region 4, Hydraulics Engineer
Long Phan – Region 4, Hydraulics
Ina Zisman – Region 4, Traffic Engineer
Dennis Allen – Region 4, Region Maintenance Superintendent
Nicholas A. Stermer – Region 4, Maintenance
Al Roys – Region 4, Maintenance
Vicky Siphler – Region 4, Maintenance
Grant Fisher – Region 4, Maintenance
Brett Locke – Region 4, Resident Engineer
Dawn Walker – Region 4, Maintenance

Table of Contents

1	INTRODUCTION	1
1.1	Bridge Characteristics and Location	1
1.2	Scour Condition and Item 113 Code	3
2	HYDROLOGY	4
2.1	Summary of Peak Flows.....	4
3	BRIDGE HYDRAULIC ANALYSIS	5
3.1	Source of Mapping and Hydraulic Model	5
3.2	Floodplain Characteristics.....	5
3.3	Hydraulic Model Results	6
4	SCOUR ANALYSIS & RESULTS	7
4.1	Site Geology	7
4.2	Scour Parameters.....	7
4.2.1	Stream Degradation	7
4.2.2	Contraction Scour.....	7
4.2.3	Pressure Scour	8
4.2.4	Pier Scour	8
4.2.5	Abutment Scour	8
4.3	Scour Results.....	9
4.4	Bridge Stability Analysis.....	12
4.5	Updated Item 113 Code.....	12
5	REFERENCES	13
APPENDICIES		
Appendix A – Site Review and Photos		
Appendix B – Existing Bridge Plans & Subsurface Information		
Appendix C – CDOT Inspection Information		
Appendix D – 1990’s CDOT & USGS Analysis		
Appendix E – Hydrologic Analysis		
Appendix F – Hydraulic Model		
Appendix G – Scour Calculations		
Appendix H – Documentation for Monitoring or Countermeasures Recommendations		
Appendix I – Bridge Stability Documentation		

1 INTRODUCTION

1.1 Bridge Characteristics and Location

The Colorado Department of Transportation (CDOT) Structure E-15-AH is a single span, steel stringer with metal plank floor, bridge. Structure E-15-AH is located in Boulder County where State Highway 170 crosses over South Boulder Creek. Table 1 presents the bridge characteristics.

Table 1
Bridge Characteristics for E-15-AH

Structure Number	E-15-AH
CDOT Region	4
County	Boulder
Feature Intersected	South Boulder Creek
Facility Carried	SH 170 ML
Mile Marker	0.4
Year Built	1930
ADT (2008)	99
Width (ft.)	16.5
Length (ft.)	41.0
Bridge Spans	1
Number of Piers	0

South Boulder Creek flows from the west to the east through the bridge section. According to the SIA report, this structure is a single span bridge. Historically, a center pier was attached to the bridge, but has since been abandoned and is not considered part of the active structure anymore, but still exists in the channel. Figure 1 and Figure 2 show the vicinity map and an aerial view of the area surrounding the structure, respectively. Figure 3 shows the downstream view of the bridge.

Figure 1
Vicinity Map (Google Earth 2012)



Figure 2
Aerial Image of E-15-AH (Google Earth 2012)



Figure 3
Looking toward the downstream face of the structure



1.2 Scour Condition and Item 113 Code


According to earlier Colorado Department of Transportation analysis, the NBI Item 113 Code for Structure E-15-AH is a U. An Item 113 Code U means that the bridge foundations are unknown and the bridge has not been evaluated for scour.

2 HYDROLOGY

2.1 Summary of Peak Flows

South Boulder Creek has a drainage area of 111 square miles at Structure E-15-AH on State Highway 170. The watershed is located 88% in the mountain hydrologic region and 12% is in the plains hydrologic region with 88% of the basin being above 7,500 feet elevation. The mean basin elevation is 9,030 feet and the mean annual precipitation is 25.85 inches. Figure 4 provides an aerial depiction of the drainage basin at Structure E-15-AH over South Boulder Creek. The Colorado StreamStats program was used to obtain the watershed characteristics parameters and peak flow estimates for flood frequency analysis.

Figure 4
Drainage Basin at E-15-AH



The peak discharges for South Boulder Creek at Structure E-15-AH are provided in Table 2. The 100-year flood peak discharge is 1,820cfs and the 500-year peak discharge is 2,500cfs. The USGS Colorado StreamStats peak flow estimates were selected for bridge hydraulic and bridge scour analysis.

Table 2
Summary of Peak Discharges


Flooding Source and Location	10-year (cfs)	50-year(cfs)	100-year (cfs)	500-year (cfs)
South Boulder Creek at SH 170	1,020	1,540	1,820	2,500

3 BRIDGE HYDRAULIC ANALYSIS

3.1 Source of Mapping and Hydraulic Model

The peak discharges presented in Table 2 were used in the hydraulic analysis. Hydrau-Tech, Inc. conducted a survey in August of 2012 which provided topographic data for construction of a hydraulic model. During this topographic survey, seven cross-sections were measured. The locations of the surveyed cross-sections are shown in Figure 5.

Figure 5
Location of surveyed cross-sections at the E-15-AH bridge site



A HEC-RAS hydraulic model was developed using the elevation data collected, along with relevant roughness values and energy loss coefficients derived from the existing conditions observed during the site visit.

3.2 Floodplain Characteristics

There are no FEMA mapping studies for South Boulder Creek in Boulder County near Structure E-15-AH; therefore, a FEMA FIRMette map could not be provided. The floodplain of South Boulder Creek at Structure E-15-AH is very narrow and consists of large boulders and trees. The stream channel itself consists of mostly large boulders to medium cobbles.

3.3 Hydraulic Model Results

Hydrau-Tech, Inc. obtained detailed topographic information needed for the hydraulic modeling through a site visit and a survey of four cross-sections upstream and three cross-sections downstream from the bridge site. These seven cross-sections were then put into the HEC-RAS program to produce the water surface profile and bridge hydraulics. This modeling provided the hydraulic data necessary for scour analysis.

Hydraulic analysis of Structure E-15-AH over South Boulder Creek was performed using HEC-RAS Version 4.1.0. For Structure E-15-AH contraction and expansion loss coefficients were chosen as 0.3 and 0.5, respectively. The selection of higher values for these loss coefficients is due to higher energy losses at the entrance and exit of the bridge site experiencing contracting and expanding flow. The cross-section orientation is looking downstream. The peak discharges for the 100-year and 500-year events presented in the Hydrology section of this report were used in hydraulic modeling. The results of this model are presented in Appendix F. The results for the 500-year event are summarized below in Table 3.

Table 3
Summary of Hydraulics – 500-Year Event

Section	Q (cfs)	WSEL (ft)	Velocity (ft/sec)	Flow Area (sq ft)	Top Width (ft)	Froude Number
319	2500.00	6042.90	7.84	427.36	130.84	0.59
293	2500.00	6043.09	5.84	589.88	170.43	0.41
214	2500.00	6042.90	6.76	530.29	89.36	0.42
141	2500.00	6042.05	9.38	356.87	54.95	0.54
122	Bridge E-15-AH					
80	2500.00	6037.63	13.45	217.09	46.57	0.94
70	2500.00	6036.86	12.74	234.42	55.89	0.97
0	2500.00	6035.21	11.35	235.59	65.67	0.97

4 SCOUR ANALYSIS & RESULTS

4.1 Site Geology

Structure E-15-AH is situated over a boulder and cobble-bed stream. Surface materials in the channel are mostly medium cobbles and boulders. No CDOT as-built drawings were available therefore there is no indication what material the foundations are set on.

4.2 Scour Parameters

As recommended by HEC-18, long-term stream degradation, contraction scour, pier scour, and abutment scour were assessed for the bridge. The median bed material size (D_{50}) for the subsurface material was field-determined to be 152.4mm. The following sections describe the development of the equation parameters for each type of scour.

4.2.1 Stream Degradation

CDOT has been taking streambed measurements at Structure E-15-AH since 1997. The depth measurements taken by CDOT for the abutments, piers, and the channel between the bridge elements are presented in Appendix C. As shown in Appendix C, the channel has experienced both degradation and aggradation of about 1 foot in the past. Because of this fluctuation in measurements, it can be said that the long term degradation of the channel is unknown according to CDOT's streambed measurements.

4.2.2 Contraction Scour

The parameters used in the contraction scour equations were determined from existing work maps and by running the 500-year flood event through the HEC-RAS model. Section 141, which is located approximately 19 feet upstream from Structure E-15-AH, was chosen as the approach cross-section. This section accurately represents the general channel geometry upstream from the bridge, and it was compared to the contracted bridge cross-section to determine the magnitude of the contraction scour.

Based on average velocity and critical velocity calculations in the approach cross-section, the clear-water contraction scour equation was used for the main channel. The width for the approach cross-section was defined as the bottom width of the channel. For the contracted bridge cross-section, the bottom deck width was used for the channel width. These widths are intended to reflect the portions of the channel which are actively mobilizing sediment. The flow area and channel flows were determined from the flow distribution within the channel widths.

Table 4 summarizes the parameters used to calculate the contraction scour for Structure E-15-AH. Variables with a subscript of 1 indicate the stream approach cross-section and variables with a subscript of 2 indicate the contracted bridge cross-section. Complete scour calculations are presented in Appendix G.

Table 4
Contraction Scour Parameters – 500-Year Event

Flow Area		Channel Flow		Channel Width		EG Slope	Correction Factor
A ₁ (ft ²)	A ₂ (ft ²)	Q ₁ (cfs)	Q ₂ (cfs)	W ₁ (ft)	W ₂ (ft)	S ₁ (ft/ft)	K ₁
210.3	248	1971.6	2500	22.3	37	0.0093	0.64

4.2.3 Pressure Scour

Pressure scour does not occur at Structure E-15-AH.

4.2.4 Pier Scour

The parameters used in the pier scour equations were determined from as-built drawings and photos and by running the 500-year event in the HEC-RAS model. The flow depth and velocity from flow distributions, as generated by HEC-RAS, were used for the flow directly upstream from the pier. The most conservative values were chosen for the K₂, K₃, and K₄ correction factors in the pier scour equation. A value of 0.9 was chosen for K₁ due to the sharp-nosed pier at Structure E-15-AH. The correction factors and other parameters used to calculate pier scour are presented in Table 5.

Table 5
Pier Scour Parameters – 500-Year Event

Pier	Flow Depth Y ₁ (ft)	Pier Width a (ft)	Mean Velocity V ₁ (ft/s)	Froude Number F _r	Correction Factors			
					K ₁	K ₂	K ₃	K ₄
2	9.7	3.0	8.5	0.48	0.9	1.0	1.1	1.0

4.2.5 Abutment Scour

Velocity, depth, and area for the flow obstructed by the abutments were computed in order to calculate abutment scour. For Structure E-15-AH, the abutment location was projected to upstream Section 141 in the HEC-RAS model, and flow distribution tables were used to find the resulting parameters. Table 6 shows the parameters used to calculate the abutment scour for the 500-year event. Complete scour calculations are presented in Appendix G.

Table 6
Abutment Scour Parameters – 500-Year Event

Abutment	Θ (deg)	L (ft)	L' (ft)	A _e (ft ²)	Q _e (cfs)
Left (1)	90	50	9.6	54.0	193.2
Right (3)	90	3.9	3.9	2.8	3.6

4.3 Scour Results


The results of the scour analysis for the 500-year event are summarized in Table 7. Figure 6 presents the theoretical scour depths from a profile view of the bridge. Detailed scour calculations are located in Appendix G.

Table 7
Summary of Scour Results – 500-Year Event


Scour Component	Long Term Degradation	Contraction			Pier Scour	Abutment Scour	
		Left Overbank	Main Channel	Right Overbank	2	Left	Right
	0.0	0.0	0.0	0.0	6.5	4.7	2.0
Total Scour (ft)					6.5	4.7	2.0

E-15-AH SCOUR PLOT

Scour Summary									
Event	Discharge	WSEL	Long Term Aggradation/ Degradation	Contraction			Abutment		Pier
				Left	Channel	Right	Left (1)	Right (3)	
500-Yr	2500 cfs	6041.41	0.0'	0.0'	0.0'	0.0'	4.7'	2.0'	6.5'



E-15-AH OVER S. BOULDER CREEK
LOOKING DOWNSTREAM



- NOTES:
- 1. TOTAL SCOUR IS THE SUMMATION OF: CONTRACTION SCOUR + ABUTMENT SCOUR + PIER SCOUR + LONG TERM AGGRADATION/DEGRADATION SCOUR AS PER FHWA EQUATIONS USING SANDBED.
 - 2. GEOLOGY INFORMATION SHOWN WAS OBTAINED FROM AS-BUILT BRIDGE PLANS.
 - 3. STATIONING INFORMATION SHOWN WAS OBTAINED FROM AS-BUILT BRIDGE PLANS.


VERTICAL DATUM SHOWN = NAVD 88

Print Date: Jun 04, 2013 4:07pm



Sheet Revisions		
Date:	Comments	Init.

Colorado Department of Transportation

 4201 East Arkansas Ave
Denver, CO 80222
Phone: 303-757-9044

Headquarters AM

As Constructed		E-15-AH SCOUR PLOT	
No Revisions:		Designer: A. MOLINAS	Structure Numbers
Revised:		Detailer: SOLLENBERGER	E-15-AH
Void:		Sheet Subset:	Subset Sheets: 10 of 13

FIGURE
6


NAME: Z:\POA 4 2013\E-15-AH South Boulder Creek\E-15-AH CAD\E-15-AH_DRAFT.dwg
PLOT DATE: Jun 04, 2013 4:07pm

NAME: E:\POA\POA 4 2013\E-15-AH South Boulder Creek\E-15-AH CAD\E-15-AH_DRAFT.dwg
PLOT DATE: Sep 09, 2013 3:04pm

PLAN VIEW FOR E-15-AH
OVER S BOULDER CREEK




HEC-RAS STATIONING





VERTICAL DATUM SHOWN = NAVD 88

Scour Summary								
Event	Discharge	WSEL	Long Term Aggradation/ Degradation	Contraction			Abutment	
				Left	Channel	Right	Left (1)	Right (3)
500-Yr	2500 cfs	6041.41	0.0'	0.0'	0.0'	0.0'	4.7'	2.0'
								6.5'



PRELIMINARY

NOT FOR CONSTRUCTION



NOTE: THIS DRAWING IS FOR PLANNING PURPOSES AND REPRESENTS CONCEPTUAL ENGINEERING. ALTERNATIVES WILL BE CONSIDERED BY CDOT PROVIDED THE ALTERNATIVE OFFERS AN EQUIVALENT INTENT OF THE PLAN. THIS DRAWING DOES NOT PROVIDE A PRELIMINARY OR FINAL DESIGN AND SHALL NOT BE USED FOR CONSTRUCTION PURPOSES.

Print Date: Sep 09, 2013 3:04pm



Sheet Revisions		
Date:	Comments	Init.

Colorado Department of Transportation
4201 East Arkansas Ave
Denver, CO 80222
Phone: 303-757-9044
Headquarters AM

As Constructed

No Revisions:

Revised:

Void:

E-15-AH
BRIDGE HYDRAULIC INFORMATION
HYDRAULIC SUMMARY

Designer: A. MOLINAS

Detailer: SOLLENBERGER

Sheet Subset:

Structure

Numbers

Subset Sheets: 11 of 13

E-15-AH

FIGURE
7

4.4 Bridge Stability Analysis

The computed scour for the 500-year flow event for Structure E-15-AH shows significant scour at the pier. However, the pier is not structurally connected to the bridge itself, it is still blocking flow in the bridge section and will therefore still cause scour. The bridge will most likely not fail under the conditions of the 500-year flow event. The theoretical scour goes to the abutment foundations. However, previously placed rip-rap along with rocks in the stream bed will protect the abutments.

4.5 Updated Item 113 Code

The NBI 113 Code for Structure E-15-AH is currently a U (Unknown foundations). Hydrau-Tech, Inc. obtained basic bridge geometry information from the SIA report and field measurements and channel geometry estimations from a survey of seven cross-sections. This information was used in conducting the hydraulic and scour analysis. Pile and foundation depths were determined by Olson Engineering through Sonic Echo testing. These test results were presented in a report by Olson Engineering and were used to determine the stability of the structure given the occurrence of the preliminary theoretical scour. The report conducted by Olson Engineering can be found in Appendix B.

We propose that the Item 113 Code for Structure E-15-AH be changed from a U to an 8. An Item 113 code of 8 means bridge foundations have been determined to be stable for calculated scour conditions; calculated scour is above the bottom of the footings. The field conditions at Structure E-15-AH showed the following:

1. The theoretical scour from the 500-year event is above the estimated footing depths.
2. The abutments have sufficient sized riprap protection to prevent abutment scour as shown in Figure A7 and A8.
3. The channel bed is comprised of cobbles and boulders and will help protect the channel bed and abutments during high flow events as shown in Figure A3.

Based on our computations and interpretations of field conditions, we propose that the current NBI Item 113 Code of U be changed to an 8 and Structure E-15-AH be taken off the scour critical bridge list.

5 REFERENCES

“Hydraulic Engineering Circular No. 18 – Evaluating Scour at Bridges – Fourth Edition,” U.S. Department of Transportation, Federal Highway Administration, May 2001.

“Hydraulic Engineering Circular No. 23 – Bridge Scour and Stream Instability Countermeasures: Experience, Selection, and Design Guidance – Third Edition,” U.S. Department of Transportation, Federal Highway Administration, September 2009.

National Oceanic and Atmospheric Administration, National Weather Service. NWS Internet Services Team “Watches, Warnings or Advisories for Colorado”
<http://alerts.weather.gov/cap/co.php?x=1>

United States Geological Survey-USGS, Colorado StreamStats.
<http://water.usgs.gov/osw/streamstats/colorado.html>

Appendix A – Site Review and Photos

Figure A.1.
Looking toward the structure entrance



Figure A.2.
Looking toward the structure outlet



Figure A.3.
Looking toward South Boulder Creek upstream from the structure



Figure A.4.
Looking toward South Boulder Creek downstream from the structure



Figure A.5.
Roadway looking toward increasing roadway station



Figure A.6.
Roadway looking toward decreasing roadway station



Figure A.7.
Looking toward the left abutment



Figure A.8.
Looking toward the right abutment



Appendix B – Existing Bridge Plans & Subsurface Information

INFRASTRUCTURE IMAGING AND NDE
ASSESSMENT, MONITORING AND REPAIR



Corporate Office:
12401 W. 49th Ave.
Wheat Ridge, CO 80033-1927 USA
phone: 303.423.1212
fax: 303.423.6071

Moser & Associates Engineering
720 S. Colorado Boulevard, Suite 410S
Denver, CO 80246

Attn: Mr. Rick Moser

Office: (303)757-3655
E-mail: moser@moser-eng.com

RE: Unknown Bridge Foundation Depth Investigation
Ultraseismic and Sonic Echo Testing
CDOT Bridge Number E-15-AH
Boulder County, Colorado
Olson Job No. 3642B

Gentlemen:

This report presents the results of Nondestructive Testing (NDT) performed on two foundation walls for Moser & Associates Engineering on CDOT bridge number E-15-AH in Boulder County, Colorado. The testing was performed on August 10, 2011 by Mr. Dennis Sack, Senior Vice President and Associate Engineer, Mr. Colin Leek, Project Engineer, and Ms. Lorae Tracy, Engineering Technician of our firm. The testing was performed with the Sonic Echo/Impulse Response (SE/IR) accompanied by the Ultraseismic (US) test method.

TESTING PROCEDURES AND LOCATIONS

US data were only collected on the West foundation wall for SE/IR data comparison and quality control purposes. The US data were collected by grease mounting a vertical accelerometer (mounted on a small aluminum block) to the side of the vertical wall to monitor the reflection of a compressional wave generated by impacting the top of the foundation wall with a 3-lb instrumented sledgehammer. The hammer input and receiver outputs from the many receiver locations (spaced evenly 12 inches apart down the side of the wall) were recorded by an Olson Instruments NDE360. The recorded receiver outputs were then analyzed in a seismic analysis software package (IX Foundation) and were stacked together much like the stacking of geophysical data. The stacking of these traces allowed for tracking of the reflected waves. In addition, the slope of coherent events in the stacked records helped to determine the velocity of the direct and reflected waves to be used in the depth calculation.

The Sonic Echo test method was also employed in this investigation on both the West and East foundation walls by mounting a single component accelerometer in a vertical orientation on the top of the respective foundation wall. A compressional wave was again generated by impacting the top of the foundation wall with a 3-lb instrumented sledgehammer (Figure 1). For the walls tested in this investigation, a representative measured compression wave velocity of 12,000 feet per second (fps) was used to compute the reflector depth which is nominally a typical velocity for concrete. It is estimated that predicted depths are accurate to within about 10% of actual values. Technical briefs describing both the Ultraseismic and Sonic Echo test methods are included in Appendix A.

TESTING RESULTS

The stacked plots for the collected US data for the West foundation wall are presented below in Figure 2. The slope of the highlighted coherent events in the stacked records determined the velocity of the direct and reflected waves used to calculate the shown pile depth. US testing on the West foundation wall showed a pile length of 16.5 ft. This depth is referenced from the top of the foundation wall.

The Sonic Echo (SE/IR) test results indicated the pile lengths, referenced from the top of the foundation wall, to be 18.2 feet for the West foundation wall and 13.7 feet for the East foundation wall. The SE plots from the SE/IR test results for these foundation walls are presented below in Figures 3 and 4. The SE/IR plots presented in this report are taken from a multitude of SE/IR test records from each pile to show the representative, average measured pile length.



Figure 1 – SE/IR Testing from the top of the East foundation wall.




Figure 2 – US data collected from Boulder county bridge number E-15-AH, West foundation wall. Apparent length is approximately 16 ½ feet.




Figure 3 - Sonic Echo data collected from Boulder county bridge number E-15-AH, second West foundation wall test. Apparent length = 18.2 feet (from top of foundation wall).




Figure 4 - Sonic Echo data collected from Boulder county bridge number E-15-AH, second East foundation wall test. Apparent length = 13.7 feet (from top of foundation wall).

CONCLUSIONS

An approximate foundation wall total height of 18 feet was measured for the West foundation wall and an approximate foundation wall height of 13 ½ feet was measured for the East foundation wall at Boulder county bridge E-15-AH. The West foundation wall height was determined by comparing the SE/IR data with the US results. The US results concluded to be less accurate than the SE/IR data due to in-situ field conditions and overall data quality. Thus only SE/IR data were collected for the East foundation wall. During data acquisition, the West foundation wall had approximately 10 ½ feet of exposed wall above grade/stream level and the East foundation wall had approximately 8 feet of exposed wall. Based on these data the West foundation wall extended 7 ½ feet into the ground and the East foundation wall extended 5 ½ feet into the ground at the time of acquisition.

A sketch of the bridge components as observed at the time of testing as well as measured with the NDE investigation is presented below in Fig. 5. As seen, the sketch includes the measured height of the abutment walls above local grade and below the bridge deck, as well as the measured depth of penetration into the subgrade of the foundation walls.




Figure 5 Sketch of Foundation Elements

Photos of the bridge elements are presented in Figs. 6-8.



Figure 6 View to West Abutment Wall (Note – visible center pier is abandoned and is not part of the active structure)



Figure 7 View to East Abutment Wall (Note – visible center pier is abandoned and is not part of the active structure)



Figure 8 Close-up View of West Abutment Wall

CLOSURE

The field portion of this NDT investigation was performed in accordance with generally accepted testing procedures. If we can provide additional information or services on this project, or additional information becomes available that would impact the findings of this investigation, please call.

Respectfully submitted,

OLSON ENGINEERING, INC.


Colin O. Leek
Project Engineer

Dennis A. Sack, P.E.
Senior Vice President, Associate Engineer

(2 copies mailed)
(1 copy e-mailed)

APPENDIX A

Appendix C – CDOT Inspection Information



Appendix D – 1990's CDOT & USGS Analysis

Colorado Department of Transportation
Structure Inspection and Inventory Report (English Units)

Highway Number (ON) 5D: 00000 1

Mile Post (ON)11: 0.400 mi

Bridge Key: E-15-AH

Inspection Date: 9/15/2009

Sufficiency Rating: 74.2 FO

Rgn/Sectn 2E/2M:	41	Hist Signif 37:	5	UW Inspection Date 93B:	
Trans Region 2T:	02	Posting status 41:	A	SI Date 93C:	
County Code 3:	013	Service on/un 42A/B:	1 5	Bridge Cost 94:	\$ 24,413
BOULDER		Main Mat/Desgn 43A/B:	3 2	Roadway Cost 95:	\$ 2,441
Place Code 4:	00000	Appr Mat/Desgn 44A/B:	0 0	Total Cost 96:	\$ 36,619
non-city		Main Spans Unit 45:	1	Year of Cost Estimate 97:	2006
Rte.(On/Under)5A:	1	Approach Spans 46:	0	Brdr Brdg Code/% 98A/B:	
Signing Prefix 5B:	7	Horiz Clr 47:	16.0 ft	Border Bridge Number 99:	
Level of Service 5C:	1	Max Span 48:	37.0 ft	Defense Highway 100:	0
Directional Suffix 5E:	0	Str Length 49:	41.0 ft	Parallel Structure 101:	N
Feature Intersected 6:		Curb Wdth L/R 50A/B:	0.0 ft 0.0 ft	Direction of Traffic 102:	3
SOUTH BOULDER CREEK		Width Curb to Curb 51:	16.0 ft	Temporary Structure 103:	
Facility Carried 7:		Width Out to Out 52:	16.5 ft	Highway System 104:	0
SH 170 ML		Deck Area:	677. sq. ft	Fed Lands Hiway 105:	0
Alias Str No.8A:		Min Clr Ovr Brdg 53:	99.99	Year Reconstructed 106:	1993
		Min Undrclr Ref 54A:	N	Deck Type 107:	6
Prll Str No. 8P		Min Undrclr 54B:	0.0 ft	Wearing Surface 108A:	7
		Min Lat Clmce Ref R 55A:	N	Membrane 108B:	0
Location 9:		Min Lat Undrclr R 55B:	0.0 ft	Deck Protection 108C:	0
0.9 MI W. OF EL DORADO SP		Min Lat Undrclr L 56:	0	Truck ADT 109:	5 %
Max Clr 10:	99.99	Deck 58:	6	Trk Net 110:	0
BaseHiway Net12:	0	Super 59:	6	Pier Protection 111:	#
IrsinvRout 13A:	00000000000	Sub 60:	6	NBIS Length 112:	Y
IrrsubRout No13B:	00	Channel/Protection 61:	8	Scour Critical 113:	U
Latitude 16:	39d 55' 51"	Culvert 62:	N	Scour Watch 113M:	
Longitude 17:	105d 17' 29"	Oprrtg Rtg Method 63:	1 LF Load Fact	Future ADT 114:	110
Range18A:	71 W	Operating Rating 64:	40.0	Year of Future ADT 115:	2028
Township18B:	71	Inv Rtg Method 65:	1	CDOT Str Type 120A:	SSM
Section18C:	25	Inventory Rating 66:	24.0	CDOT Constr Type 120B:	0.
Detour Length 19:	2.0 mi	Asph/Fill Thick 66T:	000 "in"	Inspection Indic 122A:	
Toll Facility 20:	3	Str. Evaluation 67:	6	Inspection Trip 122AA:	
Custodian 21:	1	Deck Geometry 68:	3	Scheduling Status 122B:	
Owner 22:	11	Undrclr Vert/Hor 69:	N	Maintenance Patrol 123:	13
Functional Class 26:	09	Posting 70:	5	Expansion Dev/Type124:	O
Year Built 27:	1930	Waterway Adequacy 7:	8	Brdg Rail Type/Mod 125A/B:	E 2
Lanes on 28A:	1	Approach Alignment 72:	6	Posting Trucks 129A/B/C:	0 0 0
Lanes Under 28B:	0	Type of Work 75A:	33	Str Rating Date 130:	9/24/1996
ADT 29:	99	Work Done By 75B:	1	Special Equip 133:	-1
Year of ADT 30:	2008	Length of Improvment 76:	41.0 ft	Vert Clr N/E 134A/B/C:	X 99.99 0.00
Design Load 31:	0	Insp Team Indicator 90B:	White Team (Ric	Vert Clr S/W 135A/B/C:	X 99.99 0.00
Apr Rdwy Width 32:	15.0 ft	Inspector Name 90C:	CHURCHESK	Vertical Clr Date:	1/1/1901
Median 33:	0	Frequency 91:	24 months	Weight Limit Color: 139:	0
Skew 34:	10.00 °	FC Frequency 92A:	-1	Str Billing Type:	U
Structure Flared 35:	0	UW Frequency 92B:	-1	Userkey 1 - System:	ONSY
Sfty Rail 36a/b/c/d:	0 0 0 0	SI Frequency 92C:	-1	Userkey 7-Update Indic	
Rail ht36h:	42 "in"	FC Inspection Date 93A:			

Inspector Name: CHURCHESK

Colorado Department of Transportation
Structure Inspection and Inventory Report (English Units)

Highway Number (ON) 5D: 00000 1

Mile Post (ON)11: 0.400 mi

Element Inspection Report

Elm/En	Description	Units	Total Qty	% in 1	CS 1	% in 2	CS 2	% in 3	CS 3	% in 4	CS 4	% in 5	CS 5
30/1	Corrug/Orthotpc Deck	(SF)	677	100 %	677	0 %	0	0 %	0	0 %	0	0 %	0
107/1	Paint Stl Opn Girder	(LF)	148	0 %	0	50 %	74	49 %	73	1 %	1	0 %	0
215/1	R/Conc Abutment	(LF)	35	100 %	35	0 %	0	0 %	0	0 %	0	0 %	0
310/1	Elastomeric Bearing	(EA)	8	100 %	8	0 %	0	0 %	0	0 %	0	0 %	0
326/1	Bridge Wingwalls	(EA)	4	100 %	4	0 %	0	0 %	0	0 %	0	0 %	0
332/1	Timb Bridge Railing	(LF)	82	100 %	82	0 %	0	0 %	0	0 %	0	0 %	0
501/1	Channel Cond	(EA)	1	100 %	1	0 %	0	0 %	0	0 %	0	0 %	0
504/1	BankCond	(EA)	1	100 %	1	0 %	0	0 %	0	0 %	0	0 %	0

Elem/Env	Description	Element Notes
30/1	Corrug/Orthotpc Deck	4X12 corrugated metal deck (R1 corrosion at bottoms of corrugations), with longitudinal treated timber planks as the riding surface. 3.75 inch thick timber planks are worn up to 2 inches deep in the wheel lines; (see 2005 PHOTOS). Leakage as expected.
107/1	Paint Stl Opn Girder	Light R1 to R1 corrosion on the top and bottom flanges. The paint is starting to peel, primarily along the top flanges. The bottom of the top flange of Girder A, between Abutment 1 and the dead pier, has a 12 inch long area of R2 corrosion. Gravel is spilling around the abutment backwalls at the outside corners, depositing gravel on the bottom flanges of exterior girders.
215/1	R/Conc Abutment	Old concrete with rock pockets, some pockets are patched. Abutment 2 has a 10 inch metal channel mounted horizontally on the abutment and wings, about 8 feet up from the footer, attached by earth anchors. Abutment 2 is pushed, and leans 6 inches for a 6.5 foot height, as measured with a string line and plumb bob from the edge of the steel channel (3 inch flanges). (See 2005 PHOTO and SKETCH) This 4.5 degree lean appears to be stabilized, judging from the position of the bearing bolts relative to the sole plates. Gravel is spilling around the abutment backwalls at outside corners, depositing gravel on the exterior girder bottom flanges.
310/1	Elastomeric Bearing	The bearing under Girder D at Abutment 2, is covered with gravel. Otherwise look OK.
326/1	Bridge Wingwalls	Old concrete with rock pockets. #1 Right wing has some disintegration on the top, with large aggregate exposed, approximately 10 to 20 feet from the bridge. End of #2 Rt. wing is spalling.
332/1	Timb Bridge Railing	Typical checking in rails and posts. Splintered at Abutment 2 end of left rail.
501/1	Channel Cond	South Boulder Creek. Rock and cobble bottom for swift year round flow, alignment OK. The pier in the middle of the channel extends up to within 3 inches of the girders; but does not, and was not intended to support them.
504/1	BankCond	Rocky with willows and trees, some boulders.

Colorado Department of Transportation
Structure Inspection and Inventory Report (English Units)

Highway Number (ON) 5D: 00000 1

Mile Post (ON)11: 0.400 mi

Maintenance Activity Summary

MMS Activity	Description	Recommended	Status	Target Year	Est Cost
353.02	Replace	2/7/2008	-1	2012	1000

Replace the worn planks on the deck.

357.01	Replace	2/7/2008	-1	2012	200
--------	---------	----------	----	------	-----

Remove sand and gravel from the bearing areas.

Bridge Notes

Conditions merit high fair or "6" for NBI Items 58, 59, and 60. Per Jeff Anderson 2/6/09

Colorado Department of Transportation
Structure Inspection and Inventory Report (English Units)

Highway Number (ON) 5D: 00000 1

Mile Post (ON)11: 0.400 mi

Inspection Notes

Temperature: 72 Degrees
Time: 12:20
Weather: Partly Cloudy

Scope:

☒ NBI: ☒ Element: ☐ Underwater: ☐ Fracture Critical: ☐ Other: Type: Regular NBI

Inspector: CHURCHESK

Inspection Team:

Inspection Date: 09/15/2009

Inspector

Inspector

Appendix E – Hydrologic Analysis

Drainage Basin at E-15-H (USGS StreamStats)




Table E.1.
Basin Characteristics Report (USGS StreamStats)

Parameter	Value
6-hour, 100-year precipitation, in inches	2.98
Mean basin slope computed from 10 m DEM, in percent	29.6
Area that drains to a point on a stream in square miles	111
Mean Basin Elevation in feet	9030
Mean annual precipitation, in inches	25.85
Percentage of basin above 7500 ft elevation	88.3

Table E.2.
USGS StreamStats Basin Characteristics

Peak-Flows Basin Characteristics			
88% Mountain Region Peak Flow (97.3 mi2)			
Parameter	Value	Regression Equation Valid Range	
		Min	Max
Drainage Area (square miles)	111	1	1060
Mean Basin Slope from 10m DEM (percent)	29.6	7.6	60.2
Mean Annual Precipitation (inches)	25.85	18	47
12% Plains Region Peak Flow (13.7 mi2)			
Parameter	Value	Regression Equation Valid Range	
		Min	Max
Drainage Area (square miles)	111	0.5	2930
6 Hour 100 Year Precipitation (inches)	2.98	2.4	5.1

Table E.3.
USGS StreamStats Peak-Flows Streamflow Statistics Area-Averaged

Peak-Flows Streamflow Statistics Area-Averaged			
Statistic	Flow (ft ³ /s)	Prediction Error (percent)	Equivalent years of record
PK2	545	65	
PK5	812	56	
PK10	1020	53	
PK25	1250	52	
PK50	1540	51	
PK100	1820	49	
PK200	2320	51	
PK500	2500	46	


Appendix F – Hydraulic Model

E-15-AH HEC from Survey Plan: E-15-AH Plan 01 3/13/2013


South Boulder Cr E-15-AH

Legend


- WS 500-yr
- WS 100-yr
- WS 50-yr
- WS 10-yr
- Ground




E-15-AH HEC from Survey Plan: E-15-AH Plan 01 3/13/2013




E-15-AH HEC from Survey Plan: E-15-AH Plan 01 3/13/2013




E-15-AH HEC from Survey Plan: E-15-AH Plan 01 3/13/2013




E-15-AH HEC from Survey Plan: E-15-AH Plan 01 3/13/2013




E-15-AH HEC from Survey Plan: E-15-AH Plan 01 3/13/2013




E-15-AH HEC from Survey Plan: E-15-AH Plan 01 3/13/2013




E-15-AH HEC from Survey Plan: E-15-AH Plan 01 3/13/2013



E-15-AH HEC from Survey Plan: E-15-AH Plan 01 3/13/2013



E-15-AH HEC from Survey Plan: E-15-AH Plan 01 3/13/2013



HEC-RAS Plan: Plan 01 River: South Boulder Cr Reach: E-15-AH

Reach	River Sta	Profile	Q Total	Min Ch El	W.S. Elev	Crit W.S.	E.G. Elev	E.G. Slope	Vel Chnl	Flow Area	Top Width	Froude # Chl
			(cfs)	(ft)	(ft)	(ft)	(ft)	(ft/ft)	(ft/s)	(sq ft)	(ft)	
E-15-AH	319	10-yr	1020.00	6036.71	6039.71	6039.71	6040.82	0.013435	8.76	126.65	59.99	1.00
E-15-AH	319	50-yr	1540.00	6036.71	6040.25	6040.25	6041.87	0.015041	10.63	160.24	64.18	1.10
E-15-AH	319	100-yr	1820.00	6036.71	6040.79	6040.79	6042.39	0.012013	10.64	199.55	81.37	1.01
E-15-AH	319	500-yr	2500.00	6036.71	6042.90		6043.68	0.003461	7.84	427.36	130.84	0.59
E-15-AH	293	10-yr	1020.00	6036.19	6039.34	6039.18	6040.26	0.010161	7.86	139.61	65.78	0.88
E-15-AH	293	50-yr	1540.00	6036.19	6040.46	6040.03	6041.30	0.006007	7.74	239.02	104.65	0.72
E-15-AH	293	100-yr	1820.00	6036.19	6041.31		6041.94	0.003560	6.86	333.95	118.97	0.57
E-15-AH	293	500-yr	2500.00	6036.19	6043.09		6043.50	0.001650	5.84	589.88	170.43	0.41
E-15-AH	214	10-yr	1020.00	6033.84	6038.43	6038.43	6039.52	0.008392	9.07	150.55	76.66	0.84
E-15-AH	214	50-yr	1540.00	6033.84	6040.34		6040.91	0.002921	7.10	307.75	84.70	0.53
E-15-AH	214	100-yr	1820.00	6033.84	6041.18		6041.69	0.002241	6.84	379.36	86.24	0.48
E-15-AH	214	500-yr	2500.00	6033.84	6042.90		6043.37	0.001591	6.76	530.29	89.36	0.42
E-15-AH	141	10-yr	1020.00	6031.49	6038.33	6036.51	6039.00	0.002683	6.96	178.17	41.43	0.51
E-15-AH	141	50-yr	1540.00	6031.49	6039.82	6037.65	6040.68	0.002612	8.01	243.63	46.67	0.53
E-15-AH	141	100-yr	1820.00	6031.49	6040.53	6038.18	6041.47	0.002578	8.47	277.50	49.39	0.53
E-15-AH	141	500-yr	2500.00	6031.49	6042.05	6039.27	6043.17	0.002499	9.38	356.87	54.95	0.54
E-15-AH	122		Bridge									
E-15-AH	80	10-yr	1020.00	6030.38	6034.85	6034.85	6036.49	0.011228	10.41	104.41	34.49	0.97
E-15-AH	80	50-yr	1540.00	6030.38	6035.95	6035.95	6038.00	0.010021	11.76	144.80	39.30	0.96
E-15-AH	80	100-yr	1820.00	6030.38	6036.49	6036.49	6038.71	0.009496	12.30	166.54	41.73	0.95
E-15-AH	80	500-yr	2500.00	6030.38	6037.63	6037.63	6040.22	0.008706	13.45	217.09	46.57	0.94
E-15-AH	70	10-yr	1020.00	6030.76	6034.62	6034.62	6035.96	0.011390	9.67	118.90	47.00	0.96
E-15-AH	70	50-yr	1540.00	6030.76	6035.50	6035.50	6037.19	0.010654	11.02	161.64	50.76	0.97
E-15-AH	70	100-yr	1820.00	6030.76	6035.93	6035.93	6037.78	0.010286	11.59	183.77	52.57	0.97
E-15-AH	70	500-yr	2500.00	6030.76	6036.86	6036.86	6039.05	0.009641	12.74	234.42	55.89	0.97
E-15-AH	0	10-yr	1020.00	6029.86	6033.33	6033.33	6034.47	0.013347	8.61	121.06	55.68	0.99
E-15-AH	0	50-yr	1540.00	6029.86	6034.06	6034.06	6035.52	0.011991	9.80	163.46	59.57	0.98
E-15-AH	0	100-yr	1820.00	6029.86	6034.42	6034.42	6036.03	0.011513	10.32	184.91	61.45	0.98
E-15-AH	0	500-yr	2500.00	6029.86	6035.21	6035.21	6037.14	0.010530	11.35	235.59	65.67	0.97

Appendix G – Scour Calculations

PROJECT: E-15-AH
DATE: 20-Mar-13
EVENT: 500-Year

PIER SCOUR

CSU Equation

For both Live bed and Clear water scour

$$\frac{y_s}{y_1} = 2.0 K_1 K_2 K_3 K_4 \left(\frac{a}{y_1} \right)^{0.65} Fr_1^{0.43}$$

Variable	Description	Source
y1= 9.7	Flow depth directly upstream of pier in ft	HEC-RAS
K1= 0.9	Correction factor for pier nose shape Table 6-1 (sharp nose)	Shape determined from site visit
K2= 1	Correction factor for angle of attack of flow from Table 6-2	0 degrees
K3= 1.1	Correction factor for bed condition from Table 6-3	Assumed no dunes
a= 3.00	Pier width, (ft)	Site visit
Fr1= 0.48	Froude number directly upstream of the pier (calculated)	
V1= 8.5	Mean Velocity of flow directly upstream of pier (ft/s)	HEC-RAS
D50= 152.4	Particle Size in mm	Field Determination
D95= 609.6	Particle Size in mm	Field Determination
K4 1.0	If D50<2 mm or D95<20 mm, then K4 = 1 If D50>2 mm or D95>20 mm, then K4 = 0.4(Vr)^0.15 Basically K4 is between 0.4 (min value) and 1, 1 probably is the most conservative.	
Ys= 6.5	Scour depth (ft)	

PROJECT: E-15-AH
DATE: 20-Mar-13
EVENT: 500-Year

CONTRACTION SCOUR

Live Bed

Transport of bed material in the upstream reach into the bridge cross section (HIGH VELOCITIES AND SMALL BED MATERIAL WILL CREATE LIVE BED SCOUR)

$$\frac{y_2}{y_1} = \left(\frac{Q_2}{Q_1} \right)^{6/7} \left(\frac{W_1}{W_2} \right)^{k_1}$$

VARIABLE		Description	Source
A1=	210.29	Flow area of the stream main channel (ft2)	Main channel flow area XS 4 (RAS)
A2=	170.13	Flow area of the contracted section (ft2)	Bridge opening area (RAS)
y1=	9.43	Average depth in the stream main channel, (ft)	A1/W1
y0=	8.53	Average depth in the contracted section, (ft)	A2/W2
Q1=	1971.63	Flow in the upstream channel transporting sediment, (cfs)	Main channel flow XS 4 (RAS)
Q2=	1859.95	Flow in the contracted channel, (cfs)	Flow in channel at bridge (RAS)
W1=	22.29	Bottom/top width of the upstream main channel, (ft)	Bank stationwidth XS 4 (RAS)
W2=	19.94	Bottom/top width of the main channel in the contracted section, (ft)	Bridge US section bottom deck width
S1=	0.009280	Slope of the energy grade line of the main channel (ft/ft)	Average E.G. slope upstream of bridge
omega (w)=	3.146325	Find D50 then see figure (right) - Fall velocity (ft/s)	Estimate from Site visit
V*=	1.68	Shear Velocity (ft/s)	
V*/omega(w)=	0.53		
k1=	0.64		See Table 1
y2=	9.63	Average Depth in the contracted section (scoured) (ft)	
Contraction Scour=	1.10	Average Contraction Scour Depth (ft)	
Vavg < Vc, Use Clear Water Scour Equation			

Clear-Water

VARIABLES

y0=	8.53	Average depth in the contracted section,
Q=	1859.95	Discharge through the bridge or on the setback overbank area at the bridge associated with the width W
W=	19.94	Bottom or top width of the contracted section
D50=	0.5	Median diameter (ft) - Sieve Analysis
Dm	0.6250	Diameter of the smallest non-transferable particle in the bed material (1.25 D50) in the contracted section (ft)
Ku=	0.0077	Constant (English Units)
y2=	6.93	Avg equilibrium depth in the contracted section after contraction scour (ft)
Contraction Scour=	-1.60	Average Contraction Scour Depth (ft)

PROJECT: E-15-AH
DATE: 13-May-13
EVENT: 500-Year

ABUTMENT SCOUR (Left)

Freohlich's Abutment Scour Equation

$$\frac{y_s}{y_a} = 2.27 K_1 K_2 \left(\frac{L'}{y_a} \right)^{0.43} Fr^{0.61} + 1$$

Variable		Description	Source
Sta	141	Ras Station for Computing Encroachment	RAS XS 141
S1=	0	RAS Station of Left Encroachment Begin	RAS LOB Output
S2=	28.78	Water Surface Left (or Left Encroachment End if split flow)	RAS LOB Output
K1=	0.82	Abutment shape coefficient from Table 7.1	CDOT Plans
θ=	90	Angle of Orientation of Abutment to Flow (See Figure 7.5 in HEC 18)	Site Visit
K2=	1.00	(θ/90) ^{1.3}	
L'=	9.59	Length of active flow obstructed by the embankment (ft) See Fig 7.4 in HEC 18	RAS LOB Output
Ae=	53.96	Flow area of the approach cross section obstructed by embankment (ft ²)	RAS LOB Output
Fr=	0.46088	Froude number of approach flow upstream of abutment	
Qe=	193.23	Flow obstructed by the approach abutment and approach embankment (ft ³ /s)	RAS LOB Output
y1=	8.6	Depth of flow at the abutment (ft)	RAS Model - depth at toe (US face)
v1=	3.51	Velocity upstream of the abutment (ft/s)	RAS Velocity Distribution (US face)
ya=	1.87	Average depth of flow in the floodplain (Ae/L) (ft)	
L=	28.78	Length of embankment projected normal to the flow (ft)	Survey/RAS Model
Ve=	3.58	Qe/Ae (ft/s)	
Abutment Scour (ys) =		Scour Depth (ft)	
L/Y1 =		3.35	Use Froehlich Equation

ABUTMENT SCOUR (Right)

Freohlich's Abutment Scour Equation

Variable		Description	Source
Sta	141	Ras Station for Computing Encroachment	RAS XS 141
S1=	63.36	RAS Station of Right Encroachment Begin	RAS ROB Output
S2=	67.25	Water Surface Right (or Right Encroachment End if split flow)	RAS ROB Output
K1=	1	Abutment shape coefficient from Table 7.1	CDOT Plans
θ=	90	Angle of Orientation of Abutment to Flow (See Figure 7.5 in HEC 18)	Site Visit
K2=	1.00	(θ/90) ^{1.3}	
L'=	3.89	Length of active flow obstructed by the embankment (ft) See Fig 7.4 in HEC 18	RAS ROB Output
Ae=	2.75	Flow area of the approach cross section obstructed by embankment (ft ²)	RAS ROB Output
Fr=	0.27	Froude number of approach flow upstream of abutment	
Qe=	3.57	Flow obstructed by the approach abutment and approach embankment (ft ³ /s)	RAS ROB Output
y1=	7.8	Depth of flow at the abutment (ft)	RAS Model - depth at toe (US face)
v1=	1.23	Velocity upstream of the abutment (ft/s)	RAS Velocity Distribution (US face)
ya=	0.71	Average depth of flow in the floodplain (Ae/L) (ft)	
L=	3.89	Length of embankment projected normal to the flow (ft)	
Ve=	1.30	Qe/Ae (ft/s)	
Abutment Scour (ys) =		Scour Depth (ft)	
L/Y1 =		0.5	Use Froehlich Equation

PROJECT: E-15-AH
DATE: 16-Aug-13
EVENT: 500-year event

ABUTMENT SCOUR
NCHRP 24-20 Abutment Scour Approach

$y_{max} = \alpha_A y_c$ or $y_{max} = \alpha_B y_c$
 $y_s = y_{max} - y_0$

Live Bed Conditions:
 $y_c = y_1 \left(\frac{q_{2c}}{q_1} \right)^{6/7}$

Clear Water Conditions:
 $y_c = \left(\frac{q_{2f}}{K_u D_{50}^{1/3}} \right)^{6/7}$

Variable	Description	Source
q ₁ = 88.45	Upstream unit discharge, ft ² /s (m ² /s)	HEC Output Q/W
q _{2c} = 67.57	Unit discharge in the constricted opening accounting for non-uniform flow distribution, ft ² /s (m ² /s)	HEC Output Q/W
q _{2c} /q ₁ = 0.76	Ratio of upstream unit discharge to unit discharge in the constricted opening	
Bed Conditions= C	If Live bed conditions leave blank, if clear-water conditions use "C"	
α _A or α _B = 1.20	Amplification factor for live-bed (α _A) or clear-water (α _B) conditions. From Figs. 8.9 through 8.12	Figures 8.9 through 8.12 (HEC-18)
y ₁ = 9.43	Upstream flow depth, ft (m)	HEC Output
K _u = 11.17	11.17 English units, 6.19 SI units	HEC-18
D ₅₀ = 0.500	Particle size with 50 percent finer, ft (m)	Grain size distribution
y _c = 5.70	Flow depth including clear-water contraction scour, ft (m)	HEC Output
y _{max} = 6.84	Maximum flow depth resulting from abutment scour, ft (m)	HEC Output
y ₀ (left)= 6.10	Flow depth at left abutment prior to scour, ft (m)	HEC Output
y ₀ (right)= 6.90	Flow depth at right abutment prior to scour, ft (m)	HEC Output
y _s (left)= 0.74	Left abutment scour depth, ft (m)	
y _s (right)= 0.00	Right abutment scour depth, ft (m)	

Appendix H – Documentation for Monitoring or Countermeasures Recommendations

Appendix I – Bridge Stability Documentation